

Anco BDT-150

Solutions Through Technology..... Environmentally Friendly Chemicals

Product Description

Anco BDT-150 is a specialty additive surfactant/thinner designed for use in brine diesel emulsion drilling muds. **Anco BDT-150** is designed to thin and provide rheology/viscosity control in brine diesel emulsion drilling mud packages.

Application

Anco BDT-150 is used primarily as a thinner in brine diesel emulsion systems.

Recommended Treatment

Exact dosage/loading is contingent on factors such as mud properties, rheology, and solids content; however, initial recommended dosage/loading is 0.5 ppb, and may require upwards to 2.0 ppb.

Handling

Always wear proper personal protective equipment. Avoid skin and eye contact. If skin contact occurs, remove contaminated clothing and launder before reuse and wash skin thoroughly with soap and water. If eye contact occurs, wash eyes with large amounts of water for at least 15 minutes. Only use this product in well ventilated areas with proper respiratory equipment.

See SDS for further details regarding the safe use of this product.

Storage

Store in a cool dry area, away from heat, sparks, and open flame. Keep containers sealed when not in use. Store out of direct sunlight. Avoid contact with strong oxidizers and strong acids.

Packaging

Anco BDT-150 is packaged in 275 gallon totes.

Typical Chemical and Physical Properties

Specific gravity	Approx. 1.08 @ 70°F
Ph	6.0 – 8.0
Shelf life.....	12 -18 months
Appearance	Clear Orange – Yellow liquid
Solubility.....	water soluble / oil dispersible
Flash Point	200 F