

Anco Blend Beads

Solutions Through Technology..... Environmentally Friendly Chemicals

Product Description

GSX-917-09 Horizontal Beads (Anco Blend Beads) lubricant is an environmentally safe drilling fluids additive containing a combination of different specific gravity beads for lubrication at both upper and lower points of contact in horizontal drilling. The beads are coated with a dry lubricant and wetting agent to further improve performance and minimize static electricity. These beads provide an insoluble and non-abrasive ball-bearing effect lubrication that aids in reducing torque and drag in all fluid systems.

Application

Advantages:

- Horizontal drilling – Improve sliding ability at both upper and lower points of contact, extend lateral drilling capability.
- Aids in preventing sticking.
- Aids in reducing pipe wear
- Environmentally safe

Recommended Treatment

Reduce torque & drag – 2 ppb initial, up to 10 ppb. Logging, Casing – 4 ppb spot, up to 10 ppb.

Handling

Always wear proper personal protective equipment. Avoid skin and eye contact. If skin contact occurs, wash with water immediately. If eye contact occurs, wash eyes with large amounts of water. Use only in well ventilated areas with respirator if needed. *See SDS for further details regarding the safe use of this product.*

Storage

Store in original, tightly closed container. Store in a well-ventilated place away from incompatible materials.

Packaging

GSX-917-09 Horizontal Beads (Anco Blend Beads) are packaged in 50lb sacks, 40 per pallet.

Typical Chemical and Physical Properties

Appearance	Black spheres
Crush strength, psi	>15,000
Vapor density	N/A
Specific gravity, g/cc	1.04 -3.2
Temperature stability °F.....	380